



Screwless Connectors  
Luminaire Connectors

LK 980-01/ 5

terminal block, 5 pole, insulating material: PA 6.6, fixing: screw, voltage rating: 450 V, current rating: 24 A, cross-section rating: 2.5 mm<sup>2</sup>



Order Info

reference number (ref. no.)	040015
PU	500
EAN	4028012113033

Type

type	terminal block
number of poles	5 pole
clamping units per pole	2
colour	white
cross-section rating	2.5 mm <sup>2</sup>

Technical Data

voltage rating	450 V
current rating	24 A
insulating material	PA 6.6
contact material	Spring Steel, Copper
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
stripping length	8.0-9.0 mm
internal core cross-section max.	1.5 / 2.5 mm <sup>2</sup>
external core cross-section min.	0.5 mm <sup>2</sup>
external core cross-section max.	2.5 mm <sup>2</sup>
fixing	screw
internal core cross-section min.	0.5 mm <sup>2</sup>
Type of Conductor Solid External	yes
Type of Conductor Flexible External	yes
Type of Conductor Stranded External	yes
Type of Conductor Solid Internal	yes
Type of Conductor Stranded Internal	yes

## Approvals

**acc. to EN 60998**

[Download PDF](#)

**acc. to UL**

[Download PDF](#)

## Accessories

**WKZ 980-01**

999041

**ZEL 110**

196420

**ZEL 900**

196423