



Screwless Connectors  
Luminaire Connectors

LK 980-01/ 5 printed "3 N Earth 1 2"

terminal block, 5 pole, insulating material: PA 6.6, fixing: screw,  
printing: 3 N Earth L, voltage rating: 450 V, current rating: 24 A, cross-  
section rating: 2.5 mm<sup>2</sup>



Order Info

reference number (ref. no.)	041015
PU	500
EAN	4028012100279

Type

type	terminal block
number of poles	5 pole
clamping units per pole	2
colour	white
cross-section rating	2.5 mm <sup>2</sup>
printing	3 N Earth L

Technical Data

voltage rating	450 V
current rating	24 A
insulating material	PA 6.6
contact material	Spring Steel, Copper
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
stripping length	8.0-9.0 mm
internal core cross-section max.	1.5 / 2.5 mm <sup>2</sup>
external core cross-section min.	0.5 mm <sup>2</sup>
external core cross-section max.	2.5 mm <sup>2</sup>
fixing	screw
internal core cross-section min.	0.5 mm <sup>2</sup>
Type of Conductor Solid External	yes
Type of Conductor Flexible External	yes
Type of Conductor Stranded External	yes
Type of Conductor Solid Internal	yes
Type of Conductor Stranded Internal	yes

## Approvals

---

<b>acc. to EN 60998</b>	<a href="#">Download PDF</a>
-------------------------	------------------------------

---

<b>acc. to UL</b>	<a href="#">Download PDF</a>
-------------------	------------------------------

---

## Accessories

---

<b>WKZ 980-01</b>	999041
-------------------	--------

---

<b>ZEL 110</b>	196420
----------------	--------

---

<b>ZEL 900</b>	196423
----------------	--------

---