



Screwless Connectors  
Luminaire Connectors

LK 980-01 RZ/ 5 SU printed "3 N Earth 1 2"

terminal block, 5 pole, insulating material: PA 6.6, fixing: catch pin, PE terminal: SU, printing: 3 N Earth 1 2, voltage rating: 450 V, current rating: 24 A, cross-section rating: 2.5 mm<sup>2</sup>



Order Info

|                             |               |
|-----------------------------|---------------|
| reference number (ref. no.) | 045615        |
| PU                          | 500           |
| EAN                         | 4028012113088 |

Type

|                         |                     |
|-------------------------|---------------------|
| type                    | terminal block      |
| number of poles         | 5 pole              |
| clamping units per pole | 2                   |
| colour                  | white               |
| cross-section rating    | 2.5 mm <sup>2</sup> |
| printing                | 3 N Earth 1 2       |

Technical Data

|                                     |                           |
|-------------------------------------|---------------------------|
| voltage rating                      | 450 V                     |
| current rating                      | 24 A                      |
| insulating material                 | PA 6.6                    |
| contact material                    | Spring Steel, Copper      |
| flammability rating                 | V-2                       |
| max. Ambient Temperature Operation  | 85 °C                     |
| stripping length                    | 8.0-9.0 mm                |
| internal core cross-section max.    | 1.5 / 2.5 mm <sup>2</sup> |
| external core cross-section min.    | 0.5 mm <sup>2</sup>       |
| external core cross-section max.    | 2.5 mm <sup>2</sup>       |
| fixing                              | catch pin                 |
| internal core cross-section min.    | 0.5 mm <sup>2</sup>       |
| Type of Conductor Solid External    | yes                       |
| Type of Conductor Flexible External | yes                       |
| Type of Conductor Stranded External | yes                       |
| Type of Conductor Solid Internal    | yes                       |
| Type of Conductor Stranded Internal | yes                       |
| PE terminal                         | SU                        |

## Approvals

---

|                         |                              |
|-------------------------|------------------------------|
| <b>acc. to EN 60998</b> | <a href="#">Download PDF</a> |
|-------------------------|------------------------------|

---

|                   |                              |
|-------------------|------------------------------|
| <b>acc. to UL</b> | <a href="#">Download PDF</a> |
|-------------------|------------------------------|

---

## Accessories

---

|                   |        |
|-------------------|--------|
| <b>WKZ 980-01</b> | 999041 |
|-------------------|--------|

---

|                |        |
|----------------|--------|
| <b>ZEL 110</b> | 196420 |
|----------------|--------|

---

|                |        |
|----------------|--------|
| <b>ZEL 900</b> | 196423 |
|----------------|--------|

---