



## Screwless Connectors Block Connectors

# 935

doubledeck terminal block, 5 pole, voltage rating: 450 V, current rating: 24 A, cross-section rating: 2.5 mm<sup>2</sup>



### Order Info

reference number (ref. no.)	108005
PU	500
EAN	4028012104185

### Type

type	doubledeck terminal block
number of poles	5 pole
clamping units per pole	2
colour	white
cross-section rating	2.5 mm <sup>2</sup>

### Technical Data

voltage rating	450 V
current rating	24 A
insulating material	PA 6.6
contact material	brass
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
stripping length	8.0-9.0 mm
internal core cross-section max.	2.5 mm <sup>2</sup>
external core cross-section min.	0.5 mm <sup>2</sup>
external core cross-section max.	2.5 mm <sup>2</sup>
internal core cross-section min.	0.5 mm <sup>2</sup>
Type of Conductor Solid External	yes
Type of Conductor Solid Internal	yes

### Approvals

acc. to EN 60998	<a href="#">Download PDF</a>
acc. to UL	<a href="#">Download PDF</a>
acc. to CSA	<a href="#">Download PDF</a>

## Accessories

---

**ZEL 110**

196420

---