



## Screwless Connectors Block Connectors

### 930-00/ 1

terminal block without release keys, 1 pole, voltage rating: 450 V,  
current rating: 24 A, cross-section rating: 2.5 mm<sup>2</sup>



### Order Info

<b>reference number (ref. no.)</b>	112001
<b>PU</b>	2,500
<b>EAN</b>	4028012100248

### Type

<b>type</b>	terminal block without release keys
<b>number of poles</b>	1 pole
<b>clamping units per pole</b>	2
<b>colour</b>	white
<b>cross-section rating</b>	2.5 mm <sup>2</sup>

### Technical Data

<b>voltage rating</b>	450 V
<b>current rating</b>	24 A
<b>insulating material</b>	PA 6.6
<b>contact material</b>	brass
<b>flammability rating</b>	V-2
<b>max. Ambient Temperature Operation</b>	85 °C
<b>stripping length</b>	8.0-9.0 mm
<b>internal core cross-section max.</b>	2.5 mm <sup>2</sup>
<b>external core cross-section min.</b>	0.5 mm <sup>2</sup>
<b>external core cross-section max.</b>	2.5 mm <sup>2</sup>
<b>internal core cross-section min.</b>	0.5 mm <sup>2</sup>
<b>Type of Conductor Solid External</b>	yes
<b>Type of Conductor Solid Internal</b>	yes

### Approvals

<b>acc. to EN 60998</b>	<a href="#">Download PDF</a>
<b>acc. to UL</b>	<a href="#">Download PDF</a>
<b>acc. to CSA</b>	<a href="#">Download PDF</a>