



## Screwless Connectors Block Connectors

### 930-02/ 3 printed N Earth L

terminal block with 2 release keys, 3 pole, printing: N Earth L, voltage rating: 450 V, current rating: 24 A, cross-section rating: 2.5 mm<sup>2</sup>



#### Order Info

reference number (ref. no.)	113403B1
PU	1,000

#### Type

type	terminal block with 2 release keys
number of poles	3 pole
clamping units per pole	2
colour	white
cross-section rating	2.5 mm <sup>2</sup>
printing	N Earth L

#### Technical Data

voltage rating	450 V
current rating	24 A
insulating material	PA 6.6
contact material	brass
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
stripping length	8.0-9.0 mm
internal core cross-section max.	2.5 mm <sup>2</sup>
external core cross-section min.	0.5 mm <sup>2</sup>
external core cross-section max.	2.5 mm <sup>2</sup>
internal core cross-section min.	0.5 mm <sup>2</sup>
Type of Conductor Solid External	yes
Type of Conductor Solid Internal	yes

#### Approvals

acc. to EN 60998	<a href="#">Download PDF</a>
acc. to UL	<a href="#">Download PDF</a>
acc. to CSA	<a href="#">Download PDF</a>