



Screw-Screwless Connectors

900-07 RZ/ 3

terminal block, 3 pole, fixing: catch pin, clamping units per pole: 2, voltage rating: 450 V, current rating: 17.5 A, cross-section rating external: 2.5 mm², cross-section rating internal: 1.5 mm²



Order Info

| | |
|-----------------------------|---------------|
| reference number (ref. no.) | 114803 |
| PU | 800 |
| EAN | 4028012104888 |

Type

| | |
|-------------------------|---------------------------|
| type | terminal block |
| number of poles | 3 pole |
| clamping units per pole | 2 |
| colour | white |
| cross-section rating | 1.5 / 2.5 mm ² |
| connection type | screw-screwless |

Technical Data

| | |
|-------------------------------------|---------------------|
| voltage rating | 450 V |
| current rating | 17.5 A |
| insulating material | PA 6.6 |
| contact material | Spring Steel, Steel |
| flammability rating | V-2 |
| max. Ambient Temperature Operation | 85 °C |
| Assembly Contact Screw | 0.8x4.0 / 0.5 Nm |
| wall thickness min. | 0.5 mm |
| wall thickness max. | 1.4 mm |
| internal core cross-section max. | 2.5 mm ² |
| internal stripping length | 7.0-7.5 mm |
| external stripping length | 8.0-8.5 mm |
| fixing | catch pin |
| internal core cross-section min. | 0.5 mm ² |
| Type of Conductor Solid External | yes |
| Type of Conductor Flexible External | yes |
| Type of Conductor Solid Internal | yes |
| Type of Conductor Stranded Internal | yes |
| cross-section rating external | 2.5 mm ² |

| | |
|--------------------------------------|---------------------|
| cross-section rating internal | 1.5 mm ² |
|--------------------------------------|---------------------|

Accessories

| | |
|----------------|--------|
| ZEL 110 | 196420 |
|----------------|--------|
