



## Screw Terminal Blocks

### 230/ 2

terminal block, 2 pole, insulating material: PA 6, cross-section rating: 2.5 mm<sup>2</sup>, pin spacing: 8.00 mm, fixing: screw, voltage rating: 450 V, current rating: 24.0 A



### Order Info

reference number (ref. no.)	121202
PU	3,000
EAN	4028012105168

### Type

type	terminal block
number of poles	2 pole
clamping units per pole	1
colour	natural
cross-section rating	2.5 mm <sup>2</sup>
connection type	screw

### Technical Data

voltage rating	450 V
current rating	24.0 A
insulating material	PA 6
contact material	brass
core cross-section min.	0.5 mm <sup>2</sup>
core cross-section max.	4.0 mm <sup>2</sup>
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	5.0-5.5 mm
Assembly Contact Screw	0.8x4.0 / 0.5 Nm
pin spacing	8.00 mm
fixing	screw

### Approvals

acc. to EN 60998

[Download PDF](#)

**acc. to UL** [Download PDF](#)

---

**acc. to CSA** [Download PDF](#)

---

## Accessories

---

**230 BZ/ 2** 191202

---

**ZEL 110** 196420

---