




## Screw Terminal Blocks

### 230/ 3 HT

terminal block, 3 pole, insulating material: PA 6.6-HT, cross-section rating: 2.5 mm<sup>2</sup>, pin spacing: 8.0 mm, fixing: screw, voltage rating: 450 V, current rating: 24 A



### Order Info

reference number (ref. no.)	121243
PU	2,000

### Type

type	terminal block
number of poles	3 pole
clamping units per pole	1
colour	brown
cross-section rating	2.5 mm <sup>2</sup>

### Technical Data

voltage rating	450 V
current rating	24 A
insulating material	PA 6.6-HT
contact material	brass
core cross-section min.	0.5 mm <sup>2</sup>
core cross-section max.	4.0 mm <sup>2</sup>
flammability rating	V-0
max. Ambient Temperature Operation	130 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	5.0-5.5 mm
Assembly Contact Screw	0.8x4.0 / ⌀ 0.5 Nm
pin spacing	8.0 mm
fixing	screw

### Approvals

acc. to EN 60998	<a href="#">Download PDF</a>
acc. to UL	<a href="#">Download PDF</a>
acc. to CSA	<a href="#">Download PDF</a>

## Accessories

---

**ZEL 110**

196420

---