




Screw Terminal Blocks

500/12 35 MDS

terminal block, 12 pole, insulating material: PA 6, cross-section rating: 2.5 mm², pin spacing: 10.0 mm, mounting hole diameter: 3.5 mm, centre stop (MDS): yes, fixing: screw, voltage rating: 450 V, current rating: 24 A



Order Info

reference number (ref. no.)	123312M
PU	50
EAN	4028012127788

Type

type	terminal block
number of poles	12 pole
clamping units per pole	1
colour	natural
cross-section rating	2.5 mm ²
centre stop (MDS)	yes

Technical Data

voltage rating	450 V
current rating	24 A
insulating material	PA 6
contact material	brass
core cross-section min.	0.5 mm ²
core cross-section max.	2.5 mm ²
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	7.0-7.5 mm
Assembly Contact Screw	0.8x4.0 / \cup 0.5 Nm
mounting hole diameter	3.5 mm
pin spacing	10.0 mm
fixing	screw

Approvals

acc. to EN 60998	Download PDF
acc. to UL	Download PDF
acc. to CSA	Download PDF

Accessories

500 BZ/12	191312
ABK 405/12	193212
ZEL 110	196420