



Screw Terminal Blocks

500 SK II/ 2

terminal block, 2 pole, insulating material: PA 6, cross-section rating: 2.5 mm², pin spacing: 10.00 mm, mounting hole diameter: 4.1 mm, fixing: screw, voltage rating: 450 V, current rating: 24.0 A



Order Info

| | |
|------------------------------------|---------------|
| reference number (ref. no.) | 124802 |
| PU | 1,000 |
| EAN | 4028012106066 |

Type

| | |
|--------------------------------|---------------------|
| type | terminal block |
| number of poles | 2 pole |
| clamping units per pole | 1 |
| colour | natural |
| cross-section rating | 2.5 mm ² |
| connection type | screw |

Technical Data

| | |
|---|---------------------|
| voltage rating | 450 V |
| current rating | 24.0 A |
| insulating material | PA 6 |
| contact material | brass |
| core cross-section min. | 0.5 mm ² |
| core cross-section max. | 6.0 mm ² |
| protection class | SK II |
| flammability rating | V-2 |
| min. Umgebungstemperatur | -40 °C |
| max. Ambient Temperature Operation | 85 °C |
| type of conductor solid | yes |
| type of conductor flexible | yes |
| type of conductor stranded | yes |
| stripping length | 7.0-7.5 mm |
| Assembly Contact Screw | 0.8x4.0 / ⌀ 0.5 Nm |
| mounting hole diameter | 4.1 mm |
| pin spacing | 10.00 mm |
| fixing | screw |

Approvals

| | |
|-------------------------|------------------------------|
| acc. to EN 60998 | Download PDF |
| acc. to UL | Download PDF |
| acc. to CSA | Download PDF |

Accessories

| | |
|------------------|--------|
| 500 BZ/ 2 | 191302 |
| ZEL 110 | 196420 |