



## Screw Terminal Blocks

### 500 SK II/12 MDS

terminal block, 12 pole, insulating material: PA 6, cross-section rating: 2.5 mm<sup>2</sup>, pin spacing: 10.0 mm, centre stop (MDS): yes, fixing: screw, voltage rating: 450 V, current rating: 24 A



#### Order Info

reference number (ref. no.)	124912M
PU	30
EAN	4028012102532

#### Type

type	terminal block
number of poles	12 pole
clamping units per pole	1
colour	natural
cross-section rating	2.5 mm <sup>2</sup>
centre stop (MDS)	yes

#### Technical Data

voltage rating	450 V
current rating	24 A
insulating material	PA 6
contact material	brass
core cross-section min.	0.5 mm <sup>2</sup>
core cross-section max.	2.5 mm <sup>2</sup>
protection class	SK II
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	7.0-7.5 mm
Assembly Contact Screw	0.8x4.0 / ⚙ 0.5 Nm
pin spacing	10.0 mm
fixing	screw

## Approvals

<b>acc. to EN 60998</b>	<a href="#">Download PDF</a>
<b>acc. to UL</b>	<a href="#">Download PDF</a>
<b>acc. to CSA</b>	<a href="#">Download PDF</a>

## Accessories

<b>500 BZ/12</b>	191312
<b>ZEL 110</b>	196420