



Connectors System AC 166® Classic Plug and Socket Connectors Flat Version

AC 166 BUF/315 black

socket, 3 pole, black, coding: 1 (mains), cable diameter min.: 7.5 mm, cable diameter max.: 8.5 mm, voltage rating: 250 V, current rating: 16 A, cross-section rating: 2.5 mm²



Order Info

reference number (ref. no.)	164063
PU	200
EAN	4028012107179

Type

type	socket
number of poles	3 pole
clamping units per pole	1
colour	black
coding	1 (mains)
cross-section rating	2.5 mm ²
PE function	yes
protection against incorrect plugging	yes

Technical Data

voltage rating	250 V
current rating	16 A
insulating material	PA 6.6
contact material	brass
core cross-section min.	0.5 mm ²
core cross-section max.	4.0 mm ²
impulse voltage rating	2.5 kV
flammability rating	V-2
max. Ambient Temperature Operation	70 °C
IP code	IP20
IP code when plugged	IP40
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	7.0 mm
dismantling length PE	39.0 mm

dismantling length	32.0 mm
cable diameter min.	7.5 mm
cable diameter max.	8.5 mm
strain relief	yes
upper limit temperature	100 °C

Approvals

acc. to EN 61984	Download PDF
acc. to UL	Download PDF
acc. to CSA	Download PDF

Accessories

AC 166 VSF black	169563
-------------------------	--------