



Transformer Connectors

DK 4 0 grey

feed-through connector, 1 pole, grey, voltage rating: 500 V, cross-section rating: 4.0 mm²



Order Info

| | |
|-----------------------------|---------------|
| reference number (ref. no.) | 202101 |
| PU | 500 |
| EAN | 4028012108428 |

Type

| | |
|-------------------------|------------------------|
| type | feed-through connector |
| number of poles | 1 pole |
| clamping units per pole | 1 |
| colour | grey |
| cross-section rating | 4.0 mm ² |

Technical Data

| | |
|------------------------------------|---------------------|
| voltage rating | 500 V |
| current rating | 32 A |
| insulating material | PA 6.6 |
| contact material | brass |
| core cross-section min. | 0.5 mm ² |
| core cross-section max. | 4.0 mm ² |
| flammability rating | V-2 |
| max. Ambient Temperature Operation | 85 °C |
| type of conductor solid | yes |
| type of conductor flexible | yes |
| type of conductor stranded | yes |
| stripping length | 8.5-9.0 mm |
| Assembly Contact Screw | 0.8x4.0 / ⚙ 0.8 Nm |
| wall thickness min. | 1.2 mm |
| wall thickness max. | 4.0 mm |
| housing hole diameter | 7.2 (-0.1) mm |
| pin spacing | 10.0 mm |

Approvals

| | |
|-------------------|------------------------------|
| acc. to UL | Download PDF |
|-------------------|------------------------------|

| | |
|--------------------|------------------------------|
| acc. to CSA | Download PDF |
|--------------------|------------------------------|

Accessories

| | |
|-----------------|--------|
| BZ 14 RU | 293800 |
|-----------------|--------|

| | |
|----------------|--------|
| BZ 14 U | 293300 |
|----------------|--------|
