



Screwless Connectors Block Connectors

937 B1 BD D1 D2 L1 N L2 PE L3

doubledeck terminal block, 7 pole, printing: D1 D2 L1 N L2 ⊕ L3,
voltage rating: 450 V, current rating: 24.0 A, cross-section
rating: 2.5 mm²



Order Info

reference number (ref. no.)	20354
PU	500
EAN	4028012111640

Type

type	doubledeck terminal block
number of poles	7 pole
clamping units per pole	2
colour	white
cross-section rating	2.5 mm ²
connection type	screwless
printing	D1 D2 L1 N L2 ⊕ L3

Technical Data

voltage rating	450 V
current rating	24.0 A
insulating material	PA 6.6
contact material	brass
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
stripping length	8.0-9.0 mm
wall thickness max.	1.0 mm
internal core cross-section max.	2.5 mm ²
external core cross-section min.	0.5 mm ²
external core cross-section max.	2.5 mm ²
fixing	catch pin
internal core cross-section min.	0.5 mm ²
Type of Conductor Solid External	yes
Type of Conductor Solid Internal	yes

Approvals

acc. to EN 60998

[Download PDF](#)

acc. to UL

[Download PDF](#)
