



Transformer Connectors

DK 4 Si 0 black

feed-through connector, 1 pole, black, voltage rating: 32 V, cross-section rating: 4.0 mm²



Order Info

reference number (ref. no.)	206161
PU	250
EAN	4028012108442

Type

type	feed-through connector
number of poles	1 pole
clamping units per pole	1
colour	black
cross-section rating	4.0 mm ²

Technical Data

voltage rating	32 V
current rating	15 A
insulating material	PA 6.6
contact material	brass
core cross-section min.	0.5 mm ²
core cross-section max.	4.0 mm ²
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	8.5-9.0 mm
Assembly Contact Screw	0.8x4.0 / ⚙ 0.8 Nm
wall thickness min.	1.2 mm
wall thickness max.	4.0 mm
housing hole diameter	7.2 (-0.1) mm
pin spacing	10.0 mm

Approvals

acc. to UL	Download PDF
-------------------	------------------------------

acc. to CSA	Download PDF
--------------------	------------------------------

Accessories

BZ 14 RU	293800
-----------------	--------

BZ 14 U	293300
----------------	--------
