



Screwless Connectors
Luminaire Connectors

LK 980-01 RZ/ 3 BD N PE L

terminal block, 3 pole, insulating material: PA 6.6, fixing: catch pin, voltage rating: 450 V, current rating: 24.0 A, cross-section rating: 2.5 mm²



Order Info

reference number (ref. no.)	21868
PU	500
EAN	4028012100286

Type

type	terminal block
number of poles	3 pole
clamping units per pole	2
colour	white
cross-section rating	2.5 mm ²

Technical Data

voltage rating	450 V
current rating	24.0 A
insulating material	PA 6.6
contact material	Spring Steel, Copper
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
stripping length	8.0-9.0 mm
wall thickness min.	0.5 mm
wall thickness max.	1.2 mm
internal core cross-section max.	1.5 / 2.5 mm ²
external core cross-section min.	0.5 mm ²
external core cross-section max.	2.5 mm ²
fixing	catch pin
internal core cross-section min.	0.5 mm ²
Type of Conductor Solid External	yes
Type of Conductor Flexible External	yes
Type of Conductor Solid Internal	yes
Type of Conductor Stranded Internal	yes

Approvals

acc. to EN 60998

[Download PDF](#)

acc. to UL

[Download PDF](#)

Accessories

ZEL 110

196420

ZEL 900

196423
