



## Transformer Connectors

### RKW 14 mini 0/ 2 red

terminal block lift terminals, 2 pole, red, voltage rating: 600 V, cross-section rating: 4.0 mm<sup>2</sup>



#### Order Info

reference number (ref. no.)	230182
PU	250
EAN	4028012108480

#### Type

type	terminal block lift terminals
number of poles	2 pole
clamping units per pole	1
colour	red
cross-section rating	4.0 mm <sup>2</sup>

#### Technical Data

voltage rating	600 V
current rating	32 A
insulating material	PA 6.6
contact material	brass
core cross-section min.	0.5 mm <sup>2</sup>
core cross-section max.	4.0 mm <sup>2</sup>
flammability rating	V-2
max. Ambient Temperature Operation	100 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	7.0-7.5 mm
Assembly Contact Screw	0.8x4.0 / ⚙ 0.8 Nm

#### Approvals

acc. to EN 60998	<a href="#">Download PDF</a>
acc. to UL	<a href="#">Download PDF</a>
acc. to CSA	<a href="#">Download PDF</a>

## Accessories

<b>BZ 14 RU</b>	293800
<b>BZ 14 U</b>	293300