



## PCB Terminal Blocks

### GSK 830 H/ 3 DS

terminal block horizontal, pin spacing: 5.0 mm, 3 pole, wire protector (DS): yes, insulating material: PBT, voltage rating: 250 V, current rating: 24 A, cross-section rating: 2.5 mm<sup>2</sup>

#### Order Info

reference number (ref. no.)	326503
PU	500
EAN	4028012109586

#### Type

type	terminal block horizontal
number of poles	3 pole
clamping units per pole	1
colour	blue
cross-section rating	2.5 mm <sup>2</sup>
wire protector (DS)	yes

#### Technical Data

voltage rating	250 V
current rating	24 A
insulating material	PBT
contact material	brass
core cross-section min.	0.5 mm <sup>2</sup>
core cross-section max.	2.5 mm <sup>2</sup>
flammability rating	V-0
max. Ambient Temperature Operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	4.5-5.0 mm
Assembly Contact Screw	0.6x3.5 / ⚙ 0.5 Nm
pin spacing	5.0 mm

#### Approvals

acc. to EN 60998	<a href="#">Download PDF</a>
acc. to UL	<a href="#">Download PDF</a>
acc. to CSA	<a href="#">Download PDF</a>